

FILM CLEANER 360, 350G AEROSOL

Chemwatch Independent Material Safety Data Sheet
Issue Date: 7-Feb-2011
C9317EC

CHEMWATCH 4698-47
Version No:2.0
CD 2011/1 Page 1 of 7

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

FILM CLEANER 360, 350G AEROSOL

SYNONYMS

"Product Code: 360"

PROPER SHIPPING NAME

AEROSOLS

PRODUCT USE

■ Application is by spray atomisation from a hand held aerosol pack.
Used according to manufacturer's directions.
Film and negative cleaner.

SUPPLIER


Company: JJETT Pty Ltd
Address:
84 Camp Road
Broadmeadows
VIC, 3047
Australia
Telephone: +61 3 9457 1125
Fax: +61 3 9459 7978
Email: sales@aerosolve.com.au

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

CHEMWATCH HAZARD RATINGS



RISK

Risk Codes

R12
R36
R44
R67

Risk Phrases

- Extremely flammable.
- Irritating to eyes.
- Risk of explosion if heated under confinement.
- Vapours may cause drowsiness and dizziness.

SAFETY

Safety Codes

S401

Safety Phrases

S46

- To clean the floor and all objects contaminated by this material, use water and detergent.
- If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

S60

- This material and its container must be disposed of as hazardous waste.

FILM CLEANER 360, 350G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Feb-2011

C9317EC

CHEMWATCH 4698-47

Version No:2.0

CD 2011/1 Page 2 of 7

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
isopropanol	67-63-0	>60
ingredients determined not to be hazardous [Mfr]		balance
hydrocarbon propellant	68476-85-7.	NotSpec

Section 4 - FIRST AID MEASURES

SWALLOWED

- - Not considered a normal route of entry.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If aerosols come in contact with the eyes:
- Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If solids or aerosol mists are deposited upon the skin:
- Flush skin and hair with running water (and soap if available).
- Remove any adhering solids with industrial skin cleansing cream.
- DO NOT use solvents.
- Seek medical attention in the event of irritation.

INHALED

- If aerosols, fumes or combustion products are inhaled:
- Remove to fresh air.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Treat symptomatically.
- For acute or short term repeated exposures to isopropanol:
- Rapid onset respiratory depression and hypotension indicates serious ingestions that require careful cardiac and respiratory monitoring together with immediate intravenous access.
 - Rapid absorption precludes the usefulness of emesis or lavage 2 hours post-ingestion. Activated charcoal and cathartics are not clinically useful. Ipecac is most useful when given 30 mins. post-ingestion.
 - There are no antidotes.
 - Management is supportive. Treat hypotension with fluids followed by vasopressors.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- SMALL FIRE:
 - Water spray, dry chemical or CO2
- LARGE FIRE:
- Water spray or fog.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
 - May be violently or explosively reactive.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

FIRE/EXPLOSION HAZARD

- - Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
- Combustion products include: carbon monoxide (CO), carbon dioxide (CO2), other pyrolysis products typical of burning organic material.

continued...

FILM CLEANER 360, 350G AEROSOL

Chemwatch Independent Material Safety Data Sheet
Issue Date: 7-Feb-2011
C9317EC

CHEMWATCH 4698-47
Version No:2.0
CD 2011/1 Page 3 of 7
Section 5 - FIRE FIGHTING MEASURES

FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

2YE

Personal Protective Equipment

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- - Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.

MAJOR SPILLS

- - DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Remove leaking cylinders to a safe place if possible.
- Release pressure under safe, controlled conditions by opening the valve.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- - DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- - DO NOT use aluminium or galvanised containers.
- Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- - Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	isopropanol (Isopropyl alcohol)	400	983	500	1230
Australia Exposure Standards	hydrocarbon propellant (LPG (liquified petroleum gas))	1000	1800		

continued...

FILM CLEANER 360, 350G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Feb-2011

C9317EC

CHEMWATCH 4698-47

Version No:2.0

CD 2011/1 Page 4 of 7

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

RESPIRATOR

Type AX Filter of sufficient capacity

EYE

■ - Safety glasses with side shields.

- Chemical goggles.

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

■ - No special equipment needed when handling small quantities.

- OTHERWISE:

- For potentially moderate exposures:

- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

■ No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.

- Skin cleansing cream.

- Eyewash unit.

- Do not spray on hot surfaces.

- The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.

- Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERRICK: Handbook of Reactive Chemical Hazards.

ENGINEERING CONTROLS

■ General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator.

Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear oily liquid / spray; not miscible with water.

PHYSICAL PROPERTIES

Liquid.

Gas.

Does not mix with water.

Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	- 30	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	379
Upper Explosive Limit (%)	7.5	Specific Gravity (water=1)	0.85
Lower Explosive Limit (%)	1.2	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	90 approx	Evaporation Rate	Not Available
isopropanol			
log Kow (Sangster 1997):		0.05	

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

■ - Elevated temperatures.

- Presence of open flame.

continued...

FILM CLEANER 360, 350G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Feb-2011

C9317EC

CHEMWATCH 4698-47

Version No:2.0

CD 2011/1 Page 5 of 7

Section 10 - STABILITY AND REACTIVITY

- Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

- Irritating to eyes.
- Vapours may cause dizziness or suffocation.
- Vapours may cause drowsiness and dizziness.

CHRONIC HEALTH EFFECTS

- Not applicable.

TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

- The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis.

- For isopropanol (IPA):

Acute toxicity: Isopropanol has a low order of acute toxicity. It is irritating to the eyes, but not to the skin.

ISOPROPANOL:

TOXICITY

- Oral (human) LDLo: 3570 mg/kg
- Oral (human) TDLo: 223 mg/kg
- Oral (man) TDLo: 14432 mg/kg
- Oral (rat) LD50: 5045 mg/kg
- Dermal (rabbit) LD50: 12800 mg/kg
- Oral (Human) TDLo: 14432 mg/kg
- Oral (Human) LD: 5272 mg/kg
- Oral (Human) LD: 3570 mg/kg
- Intraperitoneal (Rat) LD50: 2735 mg/kg
- Intravenous (Rat) LD50: 1088 mg/kg
- Oral (Mouse) LD50: 3600 mg/kg
- Intraperitoneal (Mouse) LD50: 4477 mg/kg
- Intravenous (Mouse) LD50: 1509 mg/kg
- Oral (Dog) LD: 1537 mg/kg
- Intravenous (Dog) LD: 1024 mg/kg
- Intravenous (Cat) LD: 1963 mg/kg
- Oral (Rabbit) LD50: 6410 mg/kg
- Intraperitoneal (Rabbit) LD50: 667 mg/kg
- Intravenous (Rabbit) LD50: 1184 mg/kg
- Intraperitoneal (Guinea pig) LD50: 2560 mg/kg
- Inhalation (Mouse) LC50: 53000 mg/m³/4h
- Oral (Rat) LD50: 5000 mg/kg
- Intraperitoneal (Rat) TDLo: 800 mg/kg
- Inhalation (Rat) LC50: 72600 mg/m³/4h
- Oral (Human) TDLo: 286 mg/kg
- Inhalation (Human) TLo: 35 ppm/4h
- Inhalation (Human) TLo: 150 ppm/2h

IRRITATION

- Skin (rabbit): 500 mg - Mild
- Eye (rabbit): 10 mg - Moderate
- Eye (rabbit): 100mg/24hr- Moderate
- Eye (rabbit): 100 mg - SEVERE

- The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

HYDROCARBON PROPELLANT:

- No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity
Ingredient

Persistence:
Water/Soil

Persistence: Air

Bioaccumulation

Mobility

continued...

FILM CLEANER 360, 350G AEROSOL

Chemwatch Independent Material Safety Data Sheet
Issue Date: 7-Feb-2011
C9317EC

CHEMWATCH 4698-47
Version No:2.0
CD 2011/1 Page 6 of 7

Section 12 - ECOLOGICAL INFORMATION

isopropanol	LOW	MED	LOW	HIGH
-------------	-----	-----	-----	------

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE GAS

HAZCHEM:

2YE (ADG7)

ADG7:

Class or division	2.1	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None
Special provisions:	63; 190; 277; 327; 344	Packing Instructions:	None
Limited quantities:	See SP 277	Portable tanks and bulk containers - Instructions:	None
Portable tanks and bulk containers - Special provisions:	None	Packagings and IBCs - Packing instruction:	P003; LP02
Packagings and IBCs - Special packing provisions:	PP17, PP87, L2		

Name and description: AEROSOLS

Land Transport UNDG:

Class or division	2.1	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None

Shipping Name:AEROSOLS

Air Transport IATA:

ICAO/IATA Class:	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	-

Special provisions: A145

Shipping Name: AEROSOLS, FLAMMABLE

Maritime Transport IMDG:

IMDG Class:	2	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F- D , S- U	Special provisions:	63 190 277 327 959

Limited Quantities: See SP277
Shipping Name: AEROSOLS 1950

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

continued...

FILM CLEANER 360, 350G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Feb-2011

C9317EC

CHEMWATCH 4698-47

Version No:2.0

CD 2011/1 Page 7 of 7

Section 15 - REGULATORY INFORMATION

isopropanol (CAS: 67-63-0) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD Representative List of High Production Volume (HPV) Chemicals"

hydrocarbon propellant (CAS: 68476-85-7,68476-86-8) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Film Cleaner 360, 350g Aerosol (CW: 4698-47)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
hydrocarbon propellant	68476- 85- 7, 68476- 86- 8

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 7-Feb-2011

Print Date: 7-Feb-2011

This is the end of the MSDS.