

STOP SET 303, 400G AEROSOL

Chemwatch Independent Material Safety Data Sheet
Issue Date: 7-Feb-2011
C9317EC

CHEMWATCH 4749-69
Version No:2.0
CD 2011/1 Page 1 of 6

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

STOP SET 303, 400G AEROSOL

SYNONYMS

"Product Code: 303"

PROPER SHIPPING NAME

AEROSOLS

PRODUCT USE

■ Application is by spray atomisation from a hand held aerosol pack.
Used according to manufacturer's directions.
Anti skinning spray for printing ink.

SUPPLIER


Company: JJETT Pty Ltd
Address:
84 Camp Road
Broadmeadows
VIC, 3047
Australia
Telephone: +61 3 9457 1125
Fax: +61 3 9459 7978
Email: sales@aerosolve.com.au

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

DANGEROUS GOODS. NON-HAZARDOUS SUBSTANCE. According to NOHSC Criteria, and ADG Code.

CHEMWATCH HAZARD RATINGS



RISK

Risk Codes
R12
R44

Risk Phrases
• Extremely flammable.
• Risk of explosion if heated under confinement.

SAFETY

Safety Codes
S16
S23
S24
S39
S26

S60

Safety Phrases
• Keep away from sources of ignition. No smoking.
• Do not breathe gas/fumes/vapour/spray.
• Avoid contact with skin.
• Wear eye/face protection.
• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
• This material and its container must be disposed of as hazardous waste.

continued...

STOP SET 303, 400G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Feb-2011

C9317EC

CHEMWATCH 4749-69

Version No:2.0

CD 2011/1 Page 2 of 6

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
alcohol		NotSpec
hydrocarbon solvent		NotSpec
additives		NotSpec
ingredients determined not to be hazardous [Mfr]		balance
hydrocarbon propellant	68476-85-7.	NotSpec

Section 4 - FIRST AID MEASURES

SWALLOWED

- - Not considered a normal route of entry.

EYE

- If aerosols come in contact with the eyes:

- Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If solids or aerosol mists are deposited upon the skin:

- Flush skin and hair with running water (and soap if available).
- Remove any adhering solids with industrial skin cleansing cream.
- DO NOT use solvents.
- Seek medical attention in the event of irritation.

INHALED

- If aerosols, fumes or combustion products are inhaled:

- Remove to fresh air.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- SMALL FIRE:

- Water spray, dry chemical or CO2

- LARGE FIRE:

- Water spray or fog.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
 - May be violently or explosively reactive.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

FIRE/EXPLOSION HAZARD

- - Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
- Combustion products include: carbon monoxide (CO), carbon dioxide (CO2), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

2YE

continued...

STOP SET 303, 400G AEROSOL

Chemwatch Independent Material Safety Data Sheet
Issue Date: 7-Feb-2011
C9317EC

CHEMWATCH 4749-69
Version No:2.0
CD 2011/1 Page 3 of 6
Section 5 - FIRE FIGHTING MEASURES

Personal Protective Equipment

Breathing apparatus.
Gas tight chemical resistant suit.
Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- - Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.

MAJOR SPILLS

- - DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Remove leaking cylinders to a safe place if possible.
- Release pressure under safe, controlled conditions by opening the valve.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- - Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- - Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- - Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³
Australia Exposure Standards	hydrocarbon propellant (LPG (liquified petroleum gas))	1000	1800

PERSONAL PROTECTION

RESPIRATOR

Type AX Filter of sufficient capacity

EYE

- No special equipment for minor exposure i.e. when handling small quantities.
- OTHERWISE: For potentially moderate or heavy exposures:
- Safety glasses with side shields.

continued...

STOP SET 303, 400G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Feb-2011

C9317EC

CHEMWATCH 4749-69

Version No:2.0

CD 2011/1 Page 4 of 6

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

HANDS/FEET

- - No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

- - The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
- Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERRICK: Handbook of Reactive Chemical Hazards.

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.

ENGINEERING CONTROLS

- General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

- Supplied as an aerosol pack. Contents under PRESSURE. Clear / white liquid / spray; not miscible with water.

PHYSICAL PROPERTIES

Liquid.
Gas.
Does not mix with water.
Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	- 30	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	379
Upper Explosive Limit (%)	7.5	Specific Gravity (water=1)	0.85
Lower Explosive Limit (%)	1.2	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	90 approx	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- - Elevated temperatures.
 - Presence of open flame.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

- Not applicable.

CHRONIC HEALTH EFFECTS

- Not applicable.

TOXICITY AND IRRITATION

HYDROCARBON PROPELLANT:

STOP SET 303, 400G AEROSOL:

- No significant acute toxicological data identified in literature search.

continued...

STOP SET 303, 400G AEROSOL

Chemwatch Independent Material Safety Data Sheet
Issue Date: 7-Feb-2011
C9317EC

CHEMWATCH 4749-69
Version No:2.0
CD 2011/1 Page 5 of 6
Section 11 - TOXICOLOGICAL INFORMATION

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE GAS

HAZCHEM:
2YE (ADG7)

ADG7:

Class or division	2.1	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None
Special provisions:	63; 190; 277; 327; 344	Packing Instructions:	None
Limited quantities:	See SP 277	Portable tanks and bulk containers - Instructions:	None
Portable tanks and bulk containers - Special provisions:	None	Packagings and IBCs - Packing instruction:	P003; LP02
Packagings and IBCs - Special packing provisions:	PP17, PP87, L2		

Name and description: AEROSOLS

Land Transport UNDG:

Class or division	2.1	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None

Shipping Name: AEROSOLS

Air Transport IATA:

ICAO/IATA Class:	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	-

Special provisions: A145

Shipping Name: AEROSOLS, FLAMMABLE

Maritime Transport IMDG:

IMDG Class:	2	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F- D , S- U	Special provisions:	63 190 277 327 959

Limited Quantities: See SP277
Shipping Name: AEROSOLS 1950

continued...

STOP SET 303, 400G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Feb-2011

C9317EC

CHEMWATCH 4749-69

Version No:2.0

CD 2011/1 Page 6 of 6

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

hydrocarbon propellant (CAS: 68476-85-7,68476-86-8) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Stop Set 303, 400g Aerosol (CW: 4749-69)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
hydrocarbon propellant	68476- 85- 7, 68476- 86- 8

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 7-Feb-2011

Print Date: 7-Feb-2011

This is the end of the MSDS.